

ZERO CLIENT

univo

UZ-100



System	
Processor	Teradici® TERA2321
Memory	
System memory	512 MB
Graphics	
Max resolution	2 x 1920 x 1200 1 x 2560 x 1600 (with special dual-link DVI cable-option) *A special dual-link DVI cable is required that connects to the two DVI ports on the w100 and outputs a dual-link DVI signal to a DVI monitor capable of supporting 2560x1600 resolution.
I/O Interfaces	
I/O ports	Front: 2 x USB-A Port (USB 2.0), 1 x Headphone port, 1 x Microphone port, Rear: 2 x USB-A Port (USB 2.0), 1 x DVI-I, 1 x DVI-D, 1 x LAN Port, 1 x DC IN, 1 x Kensington Security Slot
Networking	
Ethernet	10 M / 100 M / 1 G
Dimensions / Weight	
Dimensions	(W) 39.5 x (D) 103 x (H) 143 mm
Weight	362 g (approximate)
Environment	
Operating temperature	0°C~ 35°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Power	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	+5V DC
Software	
Protocols	VMware® Horizon View™
Regulatory	
CB, NRTL, FCC, CE, VCCI, BIS	

